

Q U O T A T I O N

Casecraft Engineering (M) Sdn Bhd (239589-D)

HQ : Lot 4.23A, 4th Floor Plaza Prima, 4 1/2 Miles, Jalan Kelang Lama, 58200,
Kuala Lumpur W.P Malaysia.
Tel : +603-7983 3384 / 82 Fax: +603-79833 394 1-700-816-382
(TOLL-FREE)

@ enquiry@casecraft.com.my www.casecraft.com.my



Date: 24 May 2021
Quote #: CE/21Q/B6168R

Att :
Galaxy Aerospace (M) Sdn Bhd
Norkatrina Kamarudin-
norkatrina@galaxyaerospace.my

Lot 11-14, MRO Centre, Malaysia
International Aerospace Centre, Sultan
Abdul Aziz Shah Airport, 47200,
47200 Subang, Selangor

Mobile : 0132676294

Qty (unit)	Item Code	Description	Unit Price (RM)	Total (RM)
3	016370-0011-110	1637AirWF,WL/NF,BLACK	RM1,900.00	RM5,700.00
1	Delivery Charges	Self Collect		

Total RM5,700.00

TERMS & CONDITION

Terms : C.O.D or bank into our Maybank account no: 514 169 174 371

Delivery: Ex-stock KL, subject prior to confirmation of sales

Validity : 30 Days

Thank you for your interest in Pelican Products !



1637

Air

Meet the lightest premium Protector™ case on the planet. Up to 40% lighter than other polymer cases.

Pelican™ Air cases are the first in a series of remarkable innovations engineered by Pelican, the pioneers of protective cases. For over 40 years Pelican has designed and crafted the most influential protective cases in the world, and we're just getting started.

With the launch of the Pelican™ Air line of cases, we're redefining the future of protection with a remarkable union of light and tough.

- Automatic Purge Valve - Keeps water and dust out while balancing air pressure
- **Watertight, crushproof, and dustproof**
- Super-light proprietary HPX2™ Polymer
- Business card holder



CONFIGURATIONS



1637
Standard



1637NF
No Foam



1637WD
With Padded Dividers



1637WF
With Foam

DIMENSIONS

Interior (L×W×D)	23.43 x 17.55" x 13.25 (59.5 x 44.6 x 33.7 cm)
Exterior (L×W×D)	26.61 x 20.65" x 14.87 (67.6 x 52.5 x 37.8 cm)
Lid Depth	2.00" (5.1 cm)
Bottom Depth	11.20" (28.4 cm)
Total Depth	13.2" (33.5 cm)
Int Volume	3.15 ft ³ (0.089 m ³)
Padlock Hole Diameter	5/16" (12.7 cm)

MATERIALS

Body	Proprietary Polypropylene Blend
Latch	ABS
O-Ring	EPDM
Purge Body	ABS
Purge Vent	Hi-Flow Gore-Tex 3 Micron Hydrophobic Non-Woven

COLORS



WEIGHT

Weight With Foam	19.40 lbs (8.8 kg)
Weight Empty	15.20 lbs (6.9 kg)
Buoyancy	209.00 lbs (94.8 kg)

TEMPERATURE

Minimum Temperature	-60°F (-51.1 °C)
Maximum Temperature	160°F (71.1 °C)

FOAM PROPERTIES

Layer 1 (Lid)	2.03" Convolute
Layer 2 (Base)	3.19" Pick N Pluck
Layer 3 (Base)	3.19" Pick N Pluck
Layer 4 (Base)	3.19" Pick N Pluck
Layer 5 (Base)	1.44" Pad

OTHER

Wheels	2
---------------	---

ACCESSORIES



1506TSA
TSA Lock



1500D
Desiccant Silica Gel



PL2
Padlock (2 pack)
