UNIT UNDER CALIBRA EQUIPMENT/TOOL ID: TEM DESCRIPTION: MODEL NO: MANUFACTURER BY: SERIAL NO: SIZE/RANGE/CAPACITY: READABILITY: RESOLUTION: THERMAL EXPANSION CALIBRATION DATE: CALIBRATION VALID UNTIL: TEMPERATURE: Min °C HUMIDITY: Min	TION	VERIFICA	Work Order N ITEM DESCRIPT PART NO: SERIAL NO: UNCERTAINTY: DRIFT:	STANDARD(S) EQUIP	PMENT USED	
EQUIPMENT/TOOL ID: TEM DESCRIPTION: MODEL NO: MANUFACTURER BY: SERIAL NO: SIZE/RANGE/CAPACITY: READABILITY: RESOLUTION: THERMAL EXPANSION CALIBRATION DATE: CALIBRATION VALID JNTIL: TEMPERATURE: Min °C	TION	VERIFICA	PART NO: SERIAL NO: UNCERTAINTY: DRIFT:	TION:	PMENT USED	
TEM DESCRIPTION: MODEL NO: MANUFACTURER BY: SERIAL NO: SIZE/RANGE/CAPACITY: READABILITY: RESOLUTION: THERMAL EXPANSION CALIBRATION DATE: CALIBRATION VALID JINTIL: TEMPERATURE: Min °C		VERIFICA	PART NO: SERIAL NO: UNCERTAINTY: DRIFT:			
MODEL NO: MANUFACTURER BY: SERIAL NO: SIZE/RANGE/CAPACITY: READABILITY: RESOLUTION: THERMAL EXPANSION CALIBRATION DATE: CALIBRATION VALID UNTIL: TEMPERATURE: Min °C		VERIFICA	SERIAL NO: UNCERTAINTY: DRIFT:			
MANUFACTURER BY: SERIAL NO: SIZE/RANGE/CAPACITY: READABILITY: RESOLUTION: THERMAL EXPANSION CALIBRATION DATE: CALIBRATION VALID UNTIL: TEMPERATURE: Min °C			UNCERTAINTY: DRIFT:	(
SERIAL NO: SIZE/RANGE/CAPACITY: READABILITY: RESOLUTION: THERMAL EXPANSION CALIBRATION DATE: CALIBRATION VALID JNTIL: TEMPERATURE: Min °C			DRIFT:	(
SIZE/RANGE/CAPACITY: READABILITY: RESOLUTION: THERMAL EXPANSION CALIBRATION DATE: CALIBRATION VALID JNTIL: TEMPERATURE: Min °C				(
READABILITY: RESOLUTION: FHERMAL EXPANSION CALIBRATION DATE: CALIBRATION VALID JNTIL: FEMPERATURE: Min °C			ATION SUMMARY	(
CALIBRATION DATE: CALIBRATION VALID JNTIL: TEMPERATURE: Min °C			ATION SUMMARY	1		
CALIBRATION DATE: CALIBRATION VALID JINTIL: TEMPERATURE: Min °C			ATION SUMMARY	(
CALIBRATION DATE: CALIBRATION VALID JNTIL: FEMPERATURE: Min °C			ATION SUMMARY	r		
CALIBRATION VALID JNTIL: EMPERATURE: Min °C			ATION SUMMARY	(
ALIBRATION VALID NTIL: EMPERATURE: Min °C		CE				
JNTIL: FEMPERATURE: Min °C			RTIFICATE NO:			
°C				BEFORE	AFTER	
	Max °C	C	CONDITION OF THE TOOL:			
% rh	Max % rh		1112 1002.			
EQUIPMENT	MODEL		PMENT USED NUMBER	CALIBRATION DUE	REMARKS	
DULL FORCE TEXTER.				DATE		
PULL FORCE TESTER:						
WIRE :						
PIN.		L				
TYPE CONDUC						
		AC	TUAL TEST			
Size No. (AWG/mm²/in²)			Continuity Test		Pass Or Fail	

	Name & Signature	Date	Company Stamp Holder
Calibrated By:			
Certified By:			