



LEONARDO MALAYSIA SDN.BHD.

# WORK CARD

SERVICE ORDER NUMBER:

90025566

WORKCARD NUMBER:

2023/BGH/001-09

TITLE:

SB139-697 DATE: NOVEMBER 22, 2022 REV. : / - ATA 25 -  
KIT LIFE RAFTS 14 PAX P/N 4G2560F01011 (PART II)

CUSTOMER:

LEONARDO HELICOPTER ITALY (LHI)

REGISTRATION:	9M-BGH	AIRFRAME HOURS:	302:40	#1 ENGINE	SERIAL NUMBER:	PCE-KB1931	#2 ENGINE	SERIAL NUMBER:	PCE-KB1885	APU	SERIAL NUMBER:	N/A
SERIAL NUMBER:	31763	LANDINGS:	850		HOURS:	302:40		HOURS:	302:40		HOURS:	N/A

NO	SOURCE	TASK / REFERENCE	REMARKS	MECHANIC SIGN	* AH SIGN & STAMP	DATE
----	--------	------------------	---------	---------------	-------------------	------

NOTE: FOR FIGURE(S), REFER TO IETP / ENGINE MANUAL / AD / SB.

### ACCOMPLISHMENT INSTRUCTIONS






#### GENERAL NOTES




- A) PLACE AN IDENTIFICATION TAG ON ALL COMPONENTS THAT ARE RE-USABLE, INCLUDING THE ATTACHING HARDWARE THAT HAS BEEN REMOVED TO GAIN ACCESS TO THE MODIFICATION AREA AND ADEQUATELY PROTECT THEM UNTIL THEIR LATER REUSE.
- B) SHAPE THE CABLES IN ORDER TO PREVENT INTERFERENCE WITH THE STRUCTURE AND THE OTHER EXISTING INSTALLATIONS, USING WHERE NECESSARY SUITABLE LACING CORDS AND PLASTIC CABLE TIEDOWN.
- C) EXERCISE EXTREME CARE DURING DRILLING OPERATIONS TO PREVENT INSTRUMENTS, CABLES AND HOSES DAMAGE.
- D) AFTER DRILLING, REMOVE ALL SWARF AND SHARP EDGES. APPLY ON BARE METAL A LIGHT FILM OF PRIMER UNLESS THE HOLE IS USED FOR GROUND CONNECTION.
- E) DURING THE INSTALLATION OF BONDING BRAIDS OR COMPONENTS REQUIRING GROUNDING, CLEAN THE SURFACE STRUCTURE IN ORDER TO OBTAIN A GOOD GROUND CONTACT.
- F) LET ADHESIVE CURE AT ROOM TEMPERATURE FOR AT LEAST 24 HOURS UNLESS OTHERWISE SPECIFIED.
- G) EXPOSED THREAD SURFACE AND NUT MUST BE PROTECTED USING A LAYER OF TECTYL ACCORDING TO MIL-C-16173 GRADE I.
- H) ALL LENGTHS ARE IN MM.

PARTS / MATERIAL USED / COMPONENT CHANGE RECORD HAVE BEEN RAISED AND ATTACHED.

CALIBRATED / SPECIAL TOOLS RECORD SHEET HAVE BEEN RAISED AND ATTACHED.

\* APPROVAL HOLDER HAVE VERIFIED THAT ALL TOOLS, EQUIPMENT AND OTHER EXTRANEIOUS PART OF MATERIALS ARE CLEARED AND ALL TASKS OR INSPECTIONS HAVE BEEN CARRIED OUT TO THE REQUIRED STANDARD. TASK HAS BEEN PERFORMED I.A.W MAINTENANCE MANUAL SPECIFIED IN WORKPACK INDEX LM/QA/GEN/01.






NO	SOURCE	TASK / REFERENCE	REMARKS	MECHANIC SIGN	* AH SIGN & STAMP	DATE
1	-	<p align="center"><b>NOTE</b></p> <p>PERFORM STEPS 1 AND 2 ONLY IF PART II OF THE PRESENT SERVICE BULLETIN IS NOT PERFORMED IMMEDIATELY AFTER PART I.</p> <p>IN ACCORDANCE WITH AMP DM 39-A-00-20-00-00A-120A-A, PREPARE THE HELICOPTER ON GROUND FOR A SAFE MAINTENANCE. DISCONNECT THE BATTERY, ALL ELECTRICAL POWER SOURCES AND/OR THE EXTERNAL POWER SUPPLY.</p>	SATISFACTORY PREPARED.			14/2/23
2	-	IN ACCORDANCE WITH AMP DM 39-A-06-41-00-00A-010A-A AND WITH REFERENCE TO FIGURES 15 THRU 19, REMOVE ALL EXTERNAL PANELS, INTERNAL PANELS AND INTERNAL LINERS AS REQUIRED TO GAIN ACCESS TO THE AREA AFFECTED BY THE INSTALLATION OF THE KIT LIFE RAFTS 14 PAX (AERAZUR) P/N 4G2560F01011.	SATISFACTORY REMOVED.			14/2/23
3	-	<p>WITH REFERENCE TO FIGURES 15 THRU 19 PERFORM THE LIFE RAFTS REMOVABLE PARTS P/N 3G2560A05911 AS DESCRIBED IN THE FOLLOWING PROCEDURE:</p> <p>3.1 WITH REFERENCE TO FIGURE 15, PERFORM LIFE RAFT LABEL INSTL P/N 3G1130A06611 AS DESCRIBED IN THE FOLLOWING PROCEDURE:</p> <p align="center"><b>NOTE</b></p> <p>THE COLOUR OF THREAD USED SHALL MATCH THE BACKGROUND COLOUR OF THE DECAL.</p> <p>3.1.1 WITH REFERENCE TO FIGURE 15 SECTION A-A, INSTALL N°2 LIFE RAFT LABELS LH P/N 3G1130A06551 IN THE INDICATED POSITIONS ON THE SOFT LINER. SEW DECALS ALL AROUND WITH COMMERCIAL NYLON THREAD.</p>	N/A DUE TO SOFT LINERS NOT FITTED TO THIS A/C	N/A		14/2/23
<input type="checkbox"/> PARTS / MATERIAL USED / COMPONENT CHANGE RECORD HAVE BEEN RAISED AND ATTACHED.			<input type="checkbox"/> CALIBRATED / SPECIAL TOOLS RECORD SHEET HAVE BEEN RAISED AND ATTACHED.			
<p>* APPROVAL HOLDER HAVE VERIFIED THAT ALL TOOLS, EQUIPMENT AND OTHER EXTRANEIOUS PART OF MATERIALS ARE CLEARED AND ALL TASKS OR INSPECTIONS HAVE BEEN CARRIED OUT TO THE REQUIRED STANDARD. TASK HAS BEEN PERFORMED I.A.W MAINTENANCE MANUAL SPECIFIED IN WORKPACK INDEX LM/QA/GEN/01.</p>						

NO	SOURCE	TASK / REFERENCE	REMARKS	MECHANIC SIGN	* AH SIGN & STAMP	DATE
		<p align="center"><b>NOTE</b></p> <p>THE COLOUR OF THREAD USED SHALL MATCH THE BACKGROUND COLOUR OF THE DECAL.</p> <p>3.1.1 WITH REFERENCE TO FIGURE 15 SECTION B-B, INSTALL N°2 LIFE RAFT LABELS RH P/N 3G1130A06451 IN THE INDICATED POSITIONS ON THE SOFT LINER. SEW DECALS ALL AROUND WITH COMMERCIAL NYLON THREAD.</p>	N/A DUE TO SOFT LINERS NOT FITTED TO THIS A/C	N/A	M 	14/2/23
		<p>3.2 WITH REFERENCE TO FIGURES 16 THRU 19, PERFORM LIFE RAFTS INSTALLATION P/N 3G2560A05811 AS DESCRIBED IN THE FOLLOWING PROCEDURE:</p> <p>3.2.1 WITH REFERENCE TO FIGURE 16 FRONT VIEW, REMOVE MLG FWD LEFT FAIRING P/N 3G5339A00754 (OR SUCCESSIVE DASHES) AND THE MLG FWD RIGHT FAIRING P/N 3G5339A00654 (OR SUCCESSIVE DASHES). DISCARD FIXING HARDWARE.</p>	SATISFACTORY REMOVED	M	M 	15/2/23
		<p>3.2.2 WITH REFERENCE TO FIGURE 16 SECTION B-B AND FIGURE 17 SECTION C-C, REMOVE EXISTING FASTENERS FROM THE INDICATED POSITIONS ON THE LEFT AND RIGHT SPONSONS.</p>	SATISFACTORY REMOVED	M	M 	15/2/23
		<p align="center"><b>NOTE</b></p> <p>PERFORM THE FOLLOWING STEP 3.2.3 ONLY IF FAIRING LIFE RAFT ASSY FWD LH P/N 3G5260A29434 AND FAIRING LIFE RAFT ASSY FWD RH P/N 3G5260A29534 ARE PROVIDED.</p>	-	-	-	-

PARTS / MATERIAL USED / COMPONENT CHANGE RECORD HAVE BEEN RAISED AND ATTACHED.

CALIBRATED / SPECIAL TOOLS RECORD SHEET HAVE BEEN RAISED AND ATTACHED.





\* APPROVAL HOLDER HAVE VERIFIED THAT ALL TOOLS, EQUIPMENT AND OTHER EXTRANEIOUS PART OF MATERIALS ARE CLEARED AND ALL TASKS OR INSPECTIONS HAVE BEEN CARRIED OUT TO THE REQUIRED STANDARD. TASK HAS BEEN PERFORMED I.A.W MAINTENANCE MANUAL SPECIFIED IN WORKPACK INDEX LM/QA/GEN/01.

NO	SOURCE	TASK / REFERENCE	REMARKS	MECHANIC SIGN	* AH SIGN & STAMP	DATE
		3.2.3 WITH REFERENCE TO FIGURES 18 AND 19, PERFORM SOFT COVER FAIRING LIFE RAFT RETRO MOD P/N 3G5260P00611 AS DESCRIBED IN THE FOLLOWING PROCEDURE:  3.2.3.1 WITH REFERENCE TO FIGURE 18 VIEW A, REMOVE N°2 EXISTING RIVET P/N MS20426AD6-7 FROM THE FAIRING LIFE RAFT ASSY FWD LH P/N 3G5260A29434.	N/A. P/N NOT PROVIDED. REFER TO NOTE.	N/A		14/2/23
		3.2.3.2 WITH REFERENCE TO FIGURE 18 VIEW A, FILL AND PLUG THE TWO EXISTING HOLES WITH ADHESIVE EA 956 AERO (C193).	N/A. REFER TO ABOVE REMARK.	N/A		14/2/23
		3.2.3.3 WITH REFERENCE TO FIGURE 18 VIEW A, APPLY N°2 PLYS OF CARBON FIBER G0801 7 1020 (C555): N°1 PLY ON EXTERNAL SURFACE AND N°1 PLY ON INTERNAL SURFACE OF THE FAIRING LIFE RAFT ASSY FWD LH P/N 3G5260A29434. BOND WITH ADHESIVE EA9309NA (C231).	N/A. REFER TO ABOVE REMARK.	N/A		14/2/23
		3.2.3.4 WITH REFERENCE TO FIGURE 18 VIEW A AND VIEW B, REMOVE THE COVER ASSY LH P/N 3G5260A36432 AND FIXING HARDWARE (N°9 RIVETS P/N MS20470A3-4 AND N°9 WASHERS P/N NAS1149CN216R) FROM THE FAIRING LIFE RAFT ASSY FWD LH P/N 3G5260A29434. CLEAN THE SURFACE.	N/A. REFER TO ABOVE REMARK.	N/A		14/2/23
		3.2.3.5 WITH REFERENCE TO FIGURE 19 VIEW C, SECTION D-D AND VIEW E, INTERPOSE ADHESIVE (C111) BETWEEN THE HANDLE COVER P/N 3G5260L02332 AND THE FAIRING LIFE RAFT ASSY FWD LH P/N 3G5260A29434 AND LOCATE THE HANDLE COVER IN THE INDICATED POSITION.	N/A. REFER TO ABOVE REMARK.	N/A		14/2/23





PARTS / MATERIAL USED / COMPONENT CHANGE RECORD HAVE BEEN RAISED AND ATTACHED.

CALIBRATED / SPECIAL TOOLS RECORD SHEET HAVE BEEN RAISED AND ATTACHED.

\* APPROVAL HOLDER HAVE VERIFIED THAT ALL TOOLS, EQUIPMENT AND OTHER EXTRANEIOUS PART OF MATERIALS ARE CLEARED AND ALL TASKS OR INSPECTIONS HAVE BEEN CARRIED OUT TO THE REQUIRED STANDARD. TASK HAS BEEN PERFORMED I.A.W MAINTENANCE MANUAL SPECIFIED IN WORKPACK INDEX LM/QA/GEN/01.

NO	SOURCE	TASK / REFERENCE	REMARKS	MECHANIC SIGN	* AH SIGN & STAMP	DATE
		<p align="center"><b>NOTE</b></p> <p>RELATE THE COVER TO EXISTING HOLES OF THE RIVETS PREVIOUSLY REMOVED.</p> <p>3.2.3.6 WITH REFERENCE TO FIGURE 19 VIEW C, SECTION D-D AND VIEW E, INSTALL THE HANDLE COVER P/N 3G5260L02332 ON THE FAIRING LIFE RAFT ASSY FWD LH P/N 3G5260A29434 BY MEANS OF N°9 RIVETS P/N A297A04TW04. FILL ALL AROUND WITH SEALANT MC-780 (C465).</p>	N/A. REFER ABOVE REMARK.	N/A		14/2/23
		<p>3.2.3.7 REPEAT STEPS 3.2.3.1 THRU 3.2.3.6 ON THE FAIRING LIFE ASSY FWD RH P/N 3G5260A29534 TO:</p> <ul style="list-style-type: none"> <li>REMOVE THE COVER ASSY RH P/N 3G5260A36532 AND INSTALL THE HANDLE COVER P/N 3G5260L02332;</li> <li>REMOVE N°2 RIVETS MS20426AD6-7 AND FILL EXISTING HOLES.</li> </ul>	REFER TO ABOVE REMARK. TASK N/A.	N/A		14/2/23
		<p align="center"><b>NOTE</b></p> <p>IF NECESSARY, REWORK SPACER THICKNESS IN ACCORDANCE WITH THE EXISTING GAP BETWEEN THE LIFE RAFT AND THE FAIRING.</p> <p>3.2.4 WITH REFERENCE TO FIGURE 16 SECTION B-B AND FIGURE 17 SECTION C-C, INTERPOSE A LAYER OF SILICONE ADHESIVE BETWEEN THE TEFLON SPACER AND THE STRUCTURE OF THE LEFT SPONSON. USE ADHESIVE RTV 732 (C126).</p>	SATISFACTORY APPLIED			17/2/23






<input type="checkbox"/> PARTS / MATERIAL USED / COMPONENT CHANGE RECORD HAVE BEEN RAISED AND ATTACHED.	<input type="checkbox"/> CALIBRATED / SPECIAL TOOLS RECORD SHEET HAVE BEEN RAISED AND ATTACHED.
* APPROVAL HOLDER HAVE VERIFIED THAT ALL TOOLS, EQUIPMENT AND OTHER EXTRANEIOUS PART OF MATERIALS ARE CLEARED AND ALL TASKS OR INSPECTIONS HAVE BEEN CARRIED OUT TO THE REQUIRED STANDARD. TASK HAS BEEN PERFORMED I.A.W MAINTENANCE MANUAL SPECIFIED IN WORKPACK INDEX LM/QA/GEN/01.	

NO	SOURCE	TASK / REFERENCE	REMARKS	MECHANIC SIGN	* AH SIGN & STAMP	DATE
		3.2.5 WITH REFERENCE TO FIGURES 16 AND 17 AND IN ACCORDANCE WITH THE APPLICABLE STEPS OF AMP DM 39-D-25-62-01-00A-720A-K, INSTALL THE LH LIFE RAFT ASSY P/N 3G2560V00531 ON THE LEFT SPONSON BY MEANS OF N°2 BOLTS P/N NAS6703-11, N°4 BOLTS P/N NAS6703-10 AND N°6 WASHERS P/N NAS1149C0316R.	SATISFACTORY INSTALLED	M	M 	17/2/23
		3.2.6 WITH REFERENCE TO FIGURE 16 SECTION B-B, TEMPORARY LOCATE THE FAIRING LIFE RAFT ASSY FWD LH P/N 3G5260A29434 OR P/N 3G5260A29435 IN POSITION ON THE LEFT SPONSON AND ENLARGE PILOT HOLES UP TO Ø5.512÷5.639 IN ACCORDANCE WITH THE EXISTING HOLES ON THE STRUCTURE.	SATISFACTORY LOCATED AND ENLARGED HOLES	M	M 	17/2/23
		3.2.7 WITH REFERENCE TO FIGURE 16 SECTION B-B, PREPARE THE SURFACE FOR BONDING IN THE INDICATED POSITION.	SATISFACTORY PREPARED	M	M 	17/2/23
		3.2.8 WITH REFERENCE TO FIGURE 16 FRONT VIEW AND SECTION B-B AND IN ACCORDANCE WITH AMP DM 39-D-25-62-06-00A-720A-K, INSTALL THE FAIRING LIFE RAFT ASSY FWD LH P/N 3G5260A29434 OR P/N 3G5260A29435 ON THE LH LIFE RAFT ASSY P/N 3G2560V00531 BY MEANS OF N°1 SCREW P/N A428A3C04, N°9 SCREWS P/N A428A3C05, N°3 SCREWS P/N A428A3C08, N°5 SCREWS P/N AN525-10R10 AND N°2 SCREWS P/N AN525-10R12.	SATISFACTORY INSTALLED	M	M 	17/2/23
		<b>NOTE</b> IF NECESSARY, REWORK SPACER THICKNESS IN ACCORDANCE WITH THE EXISTING GAP BETWEEN THE LIFE RAFT AND THE FAIRING.	-	-	-	-

PARTS / MATERIAL USED / COMPONENT CHANGE RECORD HAVE BEEN RAISED AND ATTACHED.

CALIBRATED / SPECIAL TOOLS RECORD SHEET HAVE BEEN RAISED AND ATTACHED.

\* APPROVAL HOLDER HAVE VERIFIED THAT ALL TOOLS, EQUIPMENT AND OTHER EXTRANEIOUS PART OF MATERIALS ARE CLEARED AND ALL TASKS OR INSPECTIONS HAVE BEEN CARRIED OUT TO THE REQUIRED STANDARD. TASK HAS BEEN PERFORMED I.A.W MAINTENANCE MANUAL SPECIFIED IN WORKPACK INDEX LM/QA/GEN/01.

NO	SOURCE	TASK / REFERENCE	REMARKS	MECHANIC SIGN	* AH SIGN & STAMP	DATE
		3.2.9 WITH REFERENCE TO FIGURE 16 SECTION B-B AND FIGURE 17 SECTION C-C, INTERPOSE A LAYER OF SILICONE ADHESIVE BETWEEN THE TEFLON SPACER AND THE STRUCTURE OF THE RIGHT SPONSON. USE ADHESIVE RTV 732 (C126).	SATISFACTORY APPLIED	<u>ZE</u>	<u>M</u> 	20/2/23
		3.2.10 WITH REFERENCE TO FIGURES 16 AND 17 AND IN ACCORDANCE WITH THE APPLICABLE STEPS OF AMP DM 39-D-25-62-02-00A-720A-K, INSTALL THE RH LIFE RAFT ASSY P/N 3G2560V00631 ON THE RIGHT SPONSON BY MEANS OF N°2 BOLTS P/N NAS6703-11, N°4 BOLTS P/N NAS6703-10 AND N°6 WASHERS P/N NAS1149C0316R.	SATISFACTORY INSTALLED	<u>ZE</u>	<u>M</u> 	20/2/23
		3.2.11 WITH REFERENCE TO FIGURE 16 SECTION B-B, TEMPORARY LOCATE THE FAIRING LIFE RAFT ASSY FWD RH P/N 3G5260A29534 OR P/N 3G5260A29535 IN POSITION ON THE RIGHT SPONSON AND ENLARGE PILOT HOLES UP TO Ø5.512÷5.639 IN ACCORDANCE WITH THE EXISTING HOLES ON THE STRUCTURE.	SATISFACTORY LOCATED AND ENLARGED HOLES	<u>ZE</u>	<u>M</u> 	20/2/23
		3.2.12 WITH REFERENCE TO FIGURE 16 SECTION B-B, PREPARE THE SURFACE FOR BONDING IN THE INDICATED POSITION.	SATISFACTORY PREPARED	<u>ZE</u>	<u>M</u> 	20/2/23
		3.2.13 WITH REFERENCE TO FIGURE 16 FRONT VIEW AND SECTION B-B AND IN ACCORDANCE WITH AMP DM, INSTALL THE FAIRING LIFE RAFT ASSY FWD RH P/N 3G5260A29534 OR P/N 3G5260A29535 ON THE RH LIFE RAFT ASSY P/N 3G2560V00631 BY MEANS OF N°1 SCREW P/N A428A3C04, N°9 SCREWS P/N A428A3C05, N°3 SCREWS P/N A428A3C08, N°5 SCREWS P/N AN525-10R10 AND N°2 SCREWS P/N AN525-10R12.	SATISFACTORY INSTALLED	<u>ZE</u>	<u>M</u> 	20/2/23

PARTS / MATERIAL USED / COMPONENT CHANGE RECORD HAVE BEEN RAISED AND ATTACHED.

CALIBRATED / SPECIAL TOOLS RECORD SHEET HAVE BEEN RAISED AND ATTACHED.

\* APPROVAL HOLDER HAVE VERIFIED THAT ALL TOOLS, EQUIPMENT AND OTHER EXTRANEIOUS PART OF MATERIALS ARE CLEARED AND ALL TASKS OR INSPECTIONS HAVE BEEN CARRIED OUT TO THE REQUIRED STANDARD. TASK HAS BEEN PERFORMED I.A.W MAINTENANCE MANUAL SPECIFIED IN WORKPACK INDEX LM/QA/GEN/01.

NO	SOURCE	TASK / REFERENCE	REMARKS	MECHANIC SIGN	* AH SIGN & STAMP	DATE
4	-	IN ACCORDANCE WITH AMP DM 39-A-06-41-00-00A-010A-A, RE-INSTALL ALL EXTERNAL PANELS, INTERNAL PANELS AND INTERNAL LINERS PREVIOUSLY REMOVED.	SATISFACTORY RE-INSTALLED			10/3/23
5	-	IN ACCORDANCE WITH WEIGHT AND BALANCE CHANGES, UPDATE THE CHART A (SEE ROTORCRAFT FLIGHT MANUAL, PART II, SECTION 6).	CamO SATISFACTORY UPDATED - REFER TO WIS NO: 2023/1564/ COR-129.			10/3/23
6	-	RETURN THE HELICOPTER TO FLIGHT CONFIGURATION AND RECORD FOR COMPLIANCE WITH PART II OF THIS SERVICE BULLETIN ON THE HELICOPTER LOGBOOK.	SATISFACTORY RETURNED TO FLIGHT CONFIGURATION. REFER TO UPDATE CamO			10/3/23
7	-	SEND THE ATTACHED COMPLIANCE FORM TO THE FOLLOWING MAIL BOX: <a href="mailto:ENGINEERING.SUPPORT.LHD@LEONARDO.COM">ENGINEERING.SUPPORT.LHD@LEONARDO.COM</a> AS AN ALTERNATIVE, GAIN ACCESS TO MY COMMUNICATIONS SECTION ON LEONARDO WEBPORTAL AND COMPILE THE "SERVICE BULLETIN APPLICATION COMMUNICATION".	SATISFACTORY PPTRD TO SEND THE COMPLIANCE FORM AS APPROPRIATE			10/3/23

**INDEPENDENT INSPECTION / RE-INSPECTION I.A.W MOE 2.23**

DESCRIPTION OF CRITICAL MAINTENANCE TASK REQUIREMENT AREA:

TO CHECK THE CORRECT INSTALLATION OF NO. 1 AND ELEM  
LH AND RH LIFE RAFT ASSY AND ITS SECURITY

L12  
LM

**AUTHORISATION HOLDER**

NAME	STAMP	SIGNATURE	DATE

**INDEPENDENT INSPECTOR**

NAME	STAMP	SIGNATURE	DATE

PARTS / MATERIAL USED / COMPONENT CHANGE RECORD HAVE BEEN RAISED AND ATTACHED.

CALIBRATED / SPECIAL TOOLS RECORD SHEET HAVE BEEN RAISED AND ATTACHED.

\* APPROVAL HOLDER HAVE VERIFIED THAT ALL TOOLS, EQUIPMENT AND OTHER EXTRANEIOUS PART OF MATERIALS ARE CLEARED AND ALL TASKS OR INSPECTIONS HAVE BEEN CARRIED OUT TO THE REQUIRED STANDARD. TASK HAS BEEN PERFORMED I.A.W MAINTENANCE MANUAL SPECIFIED IN WORKPACK INDEX LM/QA/GEN/01.





**PARTS / MATERIAL USED /  
COMPONENT CHANGE RECORD**

**WORKSHEET /  
WORKCARD  
NUMBER :**

2022/BGH/001-09

**SERVICE ORDER  
NUMBER :** 9 0 0 2 5

5 6 6

**AIRFRAME  
HOURS :**

302:40

**AIRCRAFT REGISTRATION :**

9M-BGH

**AIRCRAFT SERIAL NUMBER :**

31763

**LANDINGS :**

850

**PARTS / MATERIAL USED / COMPONENT CHANGE RECORD (IF APPLICABLE)**

DESCRIPTION	PART NO.	REMOVED		INSTALLED		RELEASE DOCUMENT
		SERIAL NO.	TSN/TSO	SERIAL NO.	TSN/TSO	
FAIRING LIFE RAFT ASSY FWD LH	3G5260A29435A1	N/A	N/A	N/A	N/A	AGU-2022-IT20-11685
FAIRING LIFE RAFT ASSY FWD RH	3G5260A29535A1	N/A	N/A	N/A	N/A	AGU-2022-IT20-11734
LIFE RAFT LABEL RH	3G1130A06451	N/A	N/A	N/A	N/A	AGU-2019-IT20-12526
LIFE RAFT LABEL LH	3G1130A06551	N/A	N/A	N/A	N/A	AGU-2019-IT20-20683
SCREW, MACHINE	AN525-10R12	N/A	N/A	N/A	N/A	IT20-2019-15079
SCREW, MACHINE	AN525-10R10	N/A	N/A	N/A	N/A	0071199849 / 08.07.2022
BOLT, SHEAR	NAS6703-11	N/A	N/A	N/A	N/A	0071192857 / 11.06.2022
BOLT, HEXAGONAL HEAD	NAS6703-10	N/A	N/A	N/A	N/A	0071201865 / 15.07.2022
WASHER, FLAT	NAS1149C0316R	N/A	N/A	N/A	N/A	0071045430 / 11.08.2020
SCREW, WASHER HEAD	A428A3C08	N/A	N/A	N/A	N/A	AGU-2019-IT20-16871
SCREW, WASHER HEAD	A428A3C05	N/A	N/A	N/A	N/A	AGU-2020-IT20-11993
SCREW, WASHER HEAD	A428A3C04	N/A	N/A	N/A	N/A	AGU-2021-IT20-15799
R/H AW139 LIFE RAFT	246302-0	N/A	N/A	202	NEW	109936
L/H AW139 LIFE RAFT	246301-0	N/A	N/A	196	NEW	109688
ANTI-SLIP SURFACING, SAFETY WALK	99999999000001288	N/A	N/A	N/A	N/A	IT20-2022-15595

---

---

**SERVICE BULLETIN**

**N° 139-697**

**DATE:** November 22, 2022

**REV. :** /

---

---

**TITLE**

**ATA 25 - KIT LIFE RAFTS 14 PAX P/N 4G2560F01011**

**REVISION LOG**

First Issue

---

An appropriate entry should be made in the aircraft log book upon accomplishment.  
If ownership of aircraft has changed, please, forward to new owner.

---