

PT6C-67C S/N:PCE-KB2092 FINAL ACCEPTANCE TEST RECORD

2017 DEC 18 TEST CELL : 0112 BUILD SPEC.: 1019

ENGINE TESTED AND ACCEPTED IN ACCORDANCE WITH E&TI : 668

FINAL VANE FLOW AREAS FIRST STAGE : 21513 3S7 6.85
SECOND STAGE : 21513 2S2 22.60

PERFORMANCE DATA

PERF.ACCEPTANCE MAX CONTINUOUS
SPEC ACTUAL SPEC ACTUAL

SHAFT SPEED 21000. 21000. 21000.
B.L.S. STD.DAY POWER 1300. 1300. 1000.
I.T.T. (T5A TRIMMED) DEG R 1648. 1648.
PSD (DERIVED) DEG R 1778. 1741.
MAS GEN. SPEED RPM 35800 35300.
SFC @ 18400 BTU/LB LB/SHP.HR 0.577 0.561

FUEL TYPE : CPW 204
TEST LHV : 18601. BTU/LB
S.G. :0.808 @ 45. DEG F
OIL TYPE : PWA 521 TYPE II
OIL CONSUMPTION : 0.0 LB/HR
OIL PRESSURE AT 32000 RPM : 110.4 PSI
@ OIL TEMPERATURE OF : 177.24 DEG F
I.T.T. TRIM BIAS : 52.0 DEG C @ 15 DEG C
TORQUE TRIM SLOPE : 1.017 %Q/%Q
TORQUE TRIM DATUM : -2.86 %Q

ENGINE DRY WEIGHT

SPEC ACTUAL
====
452.1 443.7

PRODUCTION SIGNATURE :

[Handwritten signature]

INSPECTION SIGNATURE :

[Handwritten signature]

GOVERNMENT INSPECTOR :

THE UNDERSIGNED CERTIFIES THAT THIS RECORD ACCURATELY SETS FORTH THE EVENTS DURING THE TEST MADE ON THE ENGINE THEREIN IDENTIFIED.

DATE 19 DEC 2017 FOREMAN, ASSY.&TEST INSP :

[Handwritten signature] TC.4-50 NO.013

D. GAUDREAU