

EUROCOPTER

REGISTRE INDIVIDUEL DE CONTROLE  
INDIVIDUAL INSPECTION LOG BOOK

APPAREIL AIRCRAFT EC 120 B  
N° SERIE SERIAL N° 1279  
PAGE 4

CONSIGNES DE NAVIGABILITE  
AIRWORTHINESS DIRECTIVES

Date edition Edition date	Consigne de nav. Airworthiness directives	Modification	SB Services bulletins	Objet Object	Application
25/07/2001	2001-318 (A)		01.00.49	DELESTEUR REF: AS21-5(1A7) AVEC NO SERIE < A 415. RELEASE REF: AS21-5(1TO7) WITH SER. NBR. BLOW AT415	NON CONCERNE. NO CONCERNED.
22/08/2001	2001-373-008 (A)			COMMANDE DE VOL DU ROTOR (ATA 67) ROTOR FLIGHT CONTROLS (ATA 67)	S/O NO SERIE APPAREIL > A 1030. NOT APPLICABLE AIRCRAFT S/N > AT 1030.
<del>05/09/2001</del> 2001-386-007			67A005	COMMANDE LACET - PROTECTION. <del>YAM CONTROL.</del>	NON APPLIQUE- APP. N < 1279. NOT EMBODIED- A/C. N < 1279. <del>Found to comply by Eurocopter</del>
18/01/1999	98.446 IMP (AB)			TRANSPONDEUR KT76A N 93000 A 1099999. TRANSPONDER KT76A N 93000 A 1099999.	NON CONCERNE. NOT CONCERNED.

Visa des Services Qualité  
Quality Department's signature



ALERT SERVICE BULLETINS ET SERVICE BULLETINS AVEC RECOMMANDATION D'APPLICATION  
ALERT SERVICE BULLETIN AND SERVICE BULLETIN WITH RECOMMANDATION FOR COMPLIANCE

No document	Code A/R/T	Modification	Consignes de nav. DGAC DGAC Airworthiness directives	Objet Object	Application
29-002	R			NOUVEAU TEMOIN DE PRECOLMATAGE COMPACT HYD. NEW WITNESS OF HYD COMPACT PRESEALING.	S.B APPLICABLE A PARTIR APPAREIL S/N 1290 S.B APPLIED FROM AIRCRAFT S/N 1290.
52A004	R1	I	2000-285-005 (A) R1	ANTI-DECONDAGE SUR RAIL SUP PORTE COULISSANTE HINGE LOSS GUARD DEVICE ON UPPER RAIL DOOR LH	REFA APPLIQUE. APPLIED REFA.
63-001	R			TROMPETTE DE LIAISON RENFORCEE BTP/GTM COUPLING FLARED ASSY STRENGTHENED MGB/ENGINE	APPLIQUE APPLIED
65-001	R			BTA AVANT BAGUES EN "TORLON". TAIL GEAR BOX WITH "TORLON" SPLIT.	APPLIQUE. APPLIED.
65-002	R			PATTES DE FIXATION DU CARTER B.T.A. ATTACH TAB OF T.G.B HOUSING.	S/O APRES N. DE SERIE M 135. NOT CONCERNED AFTER S/N N 135.
67A003	I			DBLE.FREINAGE DES AXES LIAISON CHAPES MANCH.CYCL. DBLE.LOCKING OF THE CYCL.CONTR.STICK COUPL.SCREWS	APPLIQUE A PARTIR DU NO APP. 1030. APPLIED AFTER S/N AIRCRAFT 1030.
67A005	I			CDE.VOL ROTOR : PROTECTION COMMANDE LACET. <del>ROTOR FLIGHT CONTROL: YAW CONTROL PROTECTION.</del>	<del>Complid by Ec</del> VALABLE A PARTIR DU NO SERIE APPA.1279. APPLICABLE TO AIRCRAFT SER.NBR.1279.

A = Alert ou Impératif / Alert or Mandatory  
R = avec Recommandation ou Recommandé / with Recommendation or Recommended  
T = Téléx Alert ou Téléx Service / Alert Telex or Service Telex

Visa des Services Qualité  
Quality Department's signature

