

SPM 70-43-25 APPLICATION OF SOLID FILM GRAPHITE LUBRICANT DAG-143

DISCLAIMER

The Incremental Changes published by GE Aviation are considered Instructions for Continued Airworthiness. These Incremental Changes, along with the current Manual revision and published Temporary Revisions, constitute the latest Instructions for Continued Airworthiness.

GE Designated: -CONFIDENTIAL-

The information contained in this document is GE proprietary information and is disclosed in confidence. It is the property of GE and shall not be used, disclosed to others or reproduced without the express written consent of GE, including, but without limitation, it is not to be used in the creation, manufacture, development, or derivation of any repairs, modifications, spare parts, designs, or configuration changes or to obtain FAA or any other government or regulatory approval to do so. If consent is given for reproduction in whole or in part, this notice and the notice set forth on each page of this document shall appear in any such reproduction in whole or part.

This technical data is considered subject to the Export Administration Regulations (EAR) pursuant to 15 CFR Parts 730-774. Transfer of this data by any means to a Non-U.S. Person, whether in the United States or abroad, without the proper U.S. Government authorization (e.g., License, exemption, NLR, etc.), is strictly prohibited.

Copyright (2023) General Electric Company, U.S.A.

HIGHLIGHTS

HIGHLIGHT
REFERENCE

DESCRIPTION OF CHANGE

tk70-43-25-640-007 [Technical Change: Removed procedure for the application of solid film graphite lubricant DAG-143.](#)

TASK 70-43-25-640-007

1. General.

A. This pageblock has been deleted in its entirety.

GE Designated: - CONFIDENTIAL Subject to the restrictions on the media