

<b>CAUTION: IF USING A COPY OF THIS PAGE, MAKE SURE IT HAS BEEN COPIED FROM A MANUAL THAT CONTAINS ALL THE LATEST REVISIONS</b>								
<b>M: Mandatory</b>		<b>R: Manufacturer required</b>				<b>OP: Optional</b>		
<b>Maintenance tasks</b>	<b>Task No.</b>	<b>Level</b>	<b>Periodicity</b>	<b>Tolerance</b>	<b>Unit</b>	<b>Reference Counter</b>	<b>Operating condition</b>	<b>Date/Signature</b>
Axial compressor - Inspection of the blades.	72-00-32-200-803	OP	Every 300	+30	FH	TSN	Erosive atmosphere and airframe not fitted with an adapted sand filter (a sand filter is adapted if its demonstrated filtration efficiency is $\geq 98\%$ per Standard ISO 5011 with ISO 12103 - A4 (ISO Coarse) test dust).	
<b>Component standard for above task: ALL</b> <b>Application conditions of above task: Engine installed on helicopter</b>								
Axial compressor - Inspection of the blades.	72-00-32-200-803	OP	Every 300	+30	FH	TSN	Erosive atmosphere and airframe fitted with an adapted sand filter that has a cumulated by-pass opening time $\geq 300$ hrs (a sand filter is adapted if its demonstrated filtration efficiency is $\geq 98\%$ per Standard ISO 5011 with ISO 12103 - A4 (ISO Coarse) test dust).	
<b>Component standard for above task: ALL</b> <b>Application conditions of above task: Engine installed on helicopter</b>								

Effectivity: C

The information in this manual is subject to the warning given on the information page.

05-20-10-201-835-A01

Inspection at 300 flight hours

Page 2

Dec. 30/2021